

EZGO

AUTHORISED UK DEALERS

GOLF CAR UK
.com

Express S4

CHOOSE YOUR ADVENTURE

The Express S4 passenger shuttle from E-Z-GO is a versatile buggy with comfortably seating for four and a rear seat that converts into a cargo deck so the Express S4 can also be used as a light utility vehicle.

Available with a choice of either a near-silent 48V electric drive train or a 13.5hp petrol engine, you can also customise your Express S4 with LED headlights, weather enclosures and alloy wheels

Get behind the wheel of the Express S4 and make every day tasks much more fun.

48V
DC
ELECTRIC

13.5 hp
PETROL
ENGINE

800 LB
LOAD
CAPACITY

4
PERSON
CAPACITY



GOLF CAR UK
Unit 7, The Boscombe Centre,
Mills Way, Amesbury,
Wiltshire, SP4 7SD

0345 8055 494

www.golfcaruk.com info@golfcaruk.com



CUSHMAN





Express S4[®]



FLIP-FLOP REAR SEAT & CONVERTIBLE DECK



HEADLIGHTS & BRUSH GUARD



OPTIONAL WEATHER ACCESSORIES

OPTIONS & ACCESSORIES

- Windshield
- Canopy
- Alloy wheels
- Weather enclosure
- Comfort grip steering wheel
- Taillights
- Hour meter
- Battery watering system
- Turn Signal with Four-Way Flashers
- Brakelights
- High output LED headlights
- Wheel Covers - Spoke and Chrome
- Limited Slip Differential
- Trail Tyres
- Body colour



ELECTRIC MODEL

PETROL MODEL

BODY & CHASSIS	
FRAME	Welded Steel with Powder-Coat Protection
BODY & FINISH	Injection Moulded TPO
STANDARD COLOURS	Forest Green, Patriot Blue, Champagne
SEAT COLOURS	Tan, Oyster, Black, Gray on Black, Red on Black, White on Black, White on Blue, White on Red

DIMENSIONS	
OVERALL LENGTH	108.5 in (276 cm)
OVERALL WIDTH	48.5 in (123 cm)
OVERALL HEIGHT w/ canopy	52.5 in (133 cm)
OVERALL HEIGHT w/o canopy	82 in (208 cm)
WHEEL BASE	65.5 in (166 cm)
FRONT WHEEL TRACK	38 in (97 cm)
REAR WHEEL TRACK	38 in (97 cm) 38.5 in (98 cm)
GROUND CLEARANCE	6.0 in (15 cm)

POWER		
POWER SOURCE	48 Volt DC	4 Cycle 24.5 cu in (401 cc)
VALVE TRAIN	N/A	Single Cylinder OHV
MOTOR TYPE	Shunt Wound	N/A
HORSEPOWER (KW)	3.0 hp (2.2 kW) Continuous	13.5hp (10.1kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	72 Volt	Starter/Generator. Solid State Reg.
BATTERIES (qty/type)	Six, 8 Volt Deep Cycle	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Dry Cartridge
LUBRICATION	N/A	Pressurised Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) Tank
BATTERY CHARGER	48 VDC 120 VAC, UL & CSA	N/A
SPEED CONTROLLER	250 Amp Solid State Controller	N/A
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse	Forward - Reverse
REAR AXLE RATIO	14.76:1	11.47:1 (Forward), 14.35:1 (Reverse)

PERFORMANCE		
SEATING CAPACITY	4 People	
WEIGHT W/O BATTERIES	844 lb (382 kg)	870 lb (395 kg)
CURB WEIGHT	1,210 lb (549 kg)	910 lb (413 kg)
VEHICLE LOAD CAPACITY	800 lb (360 kg)	
OUTSIDE CLEARANCE CIRCLE	20.3 ft (7.1 m)	
SPEED	17.5 mph ± 0.5 mph (28.2 kph ± 0.8 kph)	17.0 mph ± 0.5 mph (27.4 kph ± 0.8 kph)

STEERING & SUSPENSION	
STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs with Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TYRES	Trail Wolf 20x11-10

