

Comfort & convenience to spare.

Move people and equipment with ease around your facilities.



Shuttle 4.

If you need a general purpose vehicle to move goods and personnel around your facility, look no further than the Cushman Shuttle 4.

It combines four forward-facing seats with a spacious cargo bed for efficient transport of personnel and equipment. Choose from either ELiTE lithium powered by Samsung SDI Technology or a fuel-efficient 13.5 hp EFI gas engine. The Shuttle 4 keeps passengers and their gear comfortable on the move.

The Shuttle 4 has a versatile chassis, and can be easily modified with bespoke back boxes, or specific features depending on the vehicles intended job role.

The vehicle can be personalised and made more visible by adding hazard beacons, strobe lights and LED headlights if they're being used in busy or hazardous areas.



ELiTE Lithium Powered by Samsung SDI Lithium Technology



13.5 hp Electric Fuel Injection Petrol







1200lb/544kg Vehicle load capacity



Zero Battery Maintenance No terminal cleaning or watering



Cargo box capacity





Shuttle 4.



Options & Accessories.

Vehicle Specifications.


EFI PETROL

11.47:1 (Forward) 14.35:1 (Reverse)

- 5-Year Battery Warranty
- · Rearview Mirror
- Windscreen
- Canopy
- · Hour Meter
- · Individual Key Switch
- Turn Signal with Four-Way Flashers
- Brake Lights
- LED Headlights
- LED Taillights/Brake Lights
- · Wheel Covers
- Limited Slip Differential
- Additional Body Colours
- Rapid On-Board Charger (ELiTE Only)
- ELITE World Charger (ELITE Only)







DIMENSIONS	
OVERALL LENGTH	134 in (343 cm)
OVERALL WIDTH	48.5 in (123 cm)
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof)
WHEEL BASE	93.5 in (237 cm)
WHEEL TRACK	34.2 in (87 cm) Front / 38.0 in (97 cm) Rear
GROUND CLEARANCE	3.9 m (9.8 cm)

9 cu ft (.25 m3)

Wood Stake Sides

Differential w/ Helical Gears

ELITE LITHIUM

POWER		
POWER SOURCE	56.7V Li-Ion Battery	Single Cylinder OHC, 4 Cycle, 25 cu in (401cc)
HORSEPOWER (KW)	14.9 hp (11.1 kW)	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.
BATTERIES (QTY/TYPE)	56.7V Li-Ion Composite Module + Cell Model One, 12 Volt Maintenance Free	
KEY OR PEDAL START	Ped	dal
BATTERY CHARGER	56.7V, 811W World Charger, 3M Charging Cord	N/A
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse /Key Switch	Forward - Reverse

PERFORMANCE		•
SEATING CAPACITY		4 Person
WEIGHT (W/O BATTERIES)	907 lb (411.5 kg)	896 lb (406 kg)
CURB WEIGHT	988 lb (448 kg)	936 lb (425 kg)
VEHICLE LOAD CAPACITY	12	200 lb (544 kg)
BED LOAD CAPACITY		400 lb (181 kg)
OUTSIDE CLEARANCE CIRCL	.E 2	25.5 ft (7.8 m)
SPEED	14.9 mph ± 0.5 mph (24.0 kph ± 0.8 kp	oh) 14 mph ± 0.5 mph (22.5 kph ± 0.8 kph)

16.99:1

	S.	TEE	RIN	IG	&	SU	SP	ΕN	SI	ON
--	----	-----	-----	----	---	----	----	----	----	----

STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TYRES (FRONT & REAR)	18 X 8.50-8 (4-Ply Rated)

BODY & CHASSIS

CARGO DECK CAPACITY

CARGO DECK MATERIAL

TRANSAXLE

REAR AXLE RATIO

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat
BODY & FINISH	Injection Moulded TPO
STANDARD COLOURS	Patriot Blue, Forest Green, White

E & O.E.



All goods and services are supplied under Golf Car UK Ltd, terms and conditions of sales are found on our website www.golfcaruk.com.