

Reliable group transportation.

Designed for safety & comfort.



Shuttle 8.

The Cushman Shuttle™ 8 is the right choice to move large groups of people throughout a campus or facility.

With six forward facing seats and a rear-facing bench seat, the Shuttle 8 can transport up to eight people quickly and comfortably.

Available with either a maintenance-free ELiTE lithium power train activated by Samsung SDI battery technology or a fuel-efficient 13.5 hp EFI gas engine.

The Shuttle 8 can be fitted with a weather enclosure to keep the worst of the elements off the vehicles occupants during transit.



ELiTE Lithium

Powered by Samsung SDI Lithium Technology



13.5 hp

Electric Fuel Injection Petrol





1600lb/726kg

Vehicle load capacity



Zero Battery Maintenance No terminal cleaning



Speedy Charge

2x Faster charging when equipped with world charger



Shuttle 8.



Options & Accessories.

- 5-Year Battery Warranty
- Rearview Mirror
- Windscreen
- Canopy
- Hour Meter
- Individual Key Switch
- Turn Signal with Four-Way Flashers
- LED Headlights
- LED Taillights/Brake lights
- Automatic Parking Brake (ELiTE Only)
- 1600lb Vehicle Load Capacity
- Rapid On-Board Charger (ELiTE Only)
- Upgrade to 6.2 Triple Pack for Extended Range (ELITE Only)







Vehicle Specifications.

EFI PETROL

3.0 in (8 cm)

DIMENSIONS	
OVERALL LENGTH	171.3 in (435 cm)
OVERALL WIDTH	49.6 in (126 cm)
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 76.0 in (193 cm) (w/ Struts & Roof)
WHEEL BASE	125.0 in (318 cm)
WHEEL TRACK	35.2 in (90 cm) Front / 36.7 in (93 cm) Rear

400 lb (181 kg)

ELITE LITHIUM

4.4 in (11 cm)

GROUND CLEARANCE

CARGO DECK CAPACITY

POWER SOURCE	56.7V Li-Ion Battery	Single Cylinder OHC, 4 Cycle, 25 cu in (401cc)	
HORSEPOWER (KW)	14.9 hp (11.1 kW) Peak	13.5 hp (10.1 kW)	
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.	
BATTERIES (QTY/TYPE)	56.7V Li-Ion Composite Module + Cell Model	One, 12 Volt Maintenance Free	
KEY OR PEDAL START	Ped	dal	
BATTERY CHARGER	56.7V, 811W World Charger, 3M Charging Cord	N/A	
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge	
LUBRICATION	N/A	Pressurized Oil System	
OIL FILTER	N/A	Spin-On	
COOLING SYSTEM	N/A	Air Cooled	
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) Tank	
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission	
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse /Key Switch Forward - Reverse		
TRANSAXLE	Differential w/ Helical Gears		
REAR AXLE RATIO	16.99:1	11.47:1 (Forward) 14.35:1 (Reverse)	

PERFORMANCE

SEATING CAPACITY	8	Person
WEIGHT (W/O BATTERIES)	1215 lb (551 kg)	1225 lb (556 kg)
CURB WEIGHT	1289 lb (585 kg)	1265 lb (574 kg)
VEHICLE LOAD CAPACITY	1600	lb (726 kg)
BED LOAD CAPACITY	400	lb (181 kg)
OUTSIDE CLEARANCE CIRCLE	35 f	t (10.7 m)
SPEED	16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph)	16 mph ± 0.5 mph (26 kph ± 0.8 kph)

STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TYRES (FRONT & REAR)	215 / 60 - 8 (8 Ply Rated) Tires

BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat
BODY & FINISH	Injection Moulded TPO
STANDARD COLOURS	Patriot Blue, Forest Green, White, Ivory, Black

E & O.E.



All goods and services are supplied under Golf Car UK Ltd, terms and conditions of sales are found on our website www.golfcaruk.com.